

# I-40 Munstycke



Munstycke	Tryck kg	Radie m	Flöde l/min	Nederbörd mm/tim ca.
<b>15</b> Grå	3.0	15.2	45.8	12
	3.5	15.8	48.5	12
	4.0	16.2	51.0	12
	4.5	16.8	53.3	11
	5.0	17.1	55.4	11
	5.5	17.4	57.7	11
	6.0	17.7	59.6	11
	6.2	17.7	60.4	12
<b>18</b> Röd	3.0	17.4	48.3	10
	3.5	17.7	52.5	10
	4.0	18.0	56.4	10
	4.5	18.0	60.1	11
	5.0	18.3	63.7	11
	5.5	18.9	67.5	11
	6.0	19.2	70.8	12
	6.2	19.2	72.1	12
	6.5	19.5	73.9	12
<b>20</b> Mörk brun	3.5	18.3	66.2	12
	4.0	18.9	71.1	12
	4.5	19.2	75.6	12
	5.0	19.5	80.0	13
	5.5	20.1	84.7	13
	6.0	19.8	88.7	14
	6.2	19.8	90.4	14
	6.5	20.1	92.5	14
	6.9	20.1	95.7	14

Munstycke	Tryck kg	Radie m	Flöde l/min	Nederbörd mm/tim ca.
<b>23</b> Mörk grön	3.5	18.9	70.6	12
	4.0	19.5	75.8	12
	4.5	19.8	80.8	12
	5.0	20.1	85.6	13
	5.5	20.4	90.8	13
	6.0	20.7	95.1	13
	6.2	20.7	97.0	14
	6.5	20.7	99.4	14
	6.9	21.0	102.9	14
<b>25</b> Mörk blå	3.5	19.5	76.7	12
	4.0	20.1	82.1	12
	4.5	20.4	87.2	13
	5.0	20.7	92.0	13
	5.5	21.0	97.3	13
	6.0	21.3	101.7	13
	6.2	21.3	103.6	14
	6.5	21.3	106.0	14
	6.9	21.6	109.5	14
<b>28</b> Svart	3.5	19.8	95.5	15
	4.0	20.4	101.1	15
	4.5	21.0	106.4	14
	5.0	21.3	111.3	15
	5.5	21.9	116.7	15
	6.0	22.3	121.1	15
	6.2	22.3	122.9	15
	6.5	22.6	125.3	15
	6.9	23.2	128.8	14

Bilder och data enligt Hunters uppgifter  
Nederbörd är baserad på 360° spridning